



ENVIRONMENT AND PLANNING COMMITTEE

**ATTACHMENTS PROVIDED UNDER
SEPARATE COVER**

Tuesday 5 August 2025

Central Coast Council
ATTACHMENTS PROVIDED UNDER SEPARATE COVER to the
Environment and Planning Committee

To be held ,
 2 Hely Street, Wyong
 on Tuesday 5 August 2025
 Commencing at 7:00 PM

INDEX

1.5	Tuggerah Lakes Flood Study - For Public Exhibition	
	Attachment 1: Tuggerah Lakes Flood Study Review - DRAFT (Reduced Size).....	4
1.6	Review of Heritage Conservation Development Controls in Central Coast Development Control Plan 2022 - For Public Exhibition	
	Attachment 1: Draft Chapter 3.6 Heritage Conservation For Exhibition	448
	Attachment 2: Draft Chapter 4.5 Wyong Town Centre For Exhibition	508
	Attachment 3: Draft Chapter 5.4 Kincumber Avoca Drive (Manassah Frost House).....	570
	Attachment 4: Draft Chapter 3.6 Heritage Conservation Track Changes - For Exhibition.....	573
	Attachment 5: Draft Chapter 4.5 Wyong Town Centre Track Changes - For Exhibition.....	662
	Attachment 6: Draft Chapter 5.4 Kincumber Avoca Drive (Manassah Frost House) Track Changes - For Exhibition.....	724
1.7	Review of Open Pile Burning Policy	
	Attachment 1: Draft Open Pile Burn Policy 2025.....	727
1.8	Revocation of Operation of Temporary Food Premises Policy	
	Attachment 1: Operation of Temporary Food Premises Policy WSC 2014	737
1.10	Local Planning Panel - Development Application Submissions Policy For Adoption	
	Attachment 1: Attachment 1 - Draft Development Assessment Submissions Policy for Adoption v1.1.....	741
	Attachment 2: Attachment 2 - Summary of Submission - Local Planning Panel Submissions Policy Report	748
1.12	2025-26 Regulatory Priorities Statement - For Adoption	

Attachment 1: CC Draft Regulatory Priorities Statement 2025 - 2026
.....752

1.16 Appointment of Community Representatives to the Coastal, Estuary and Floodplain Risk Management Sub-Committee

Attachment 2: Draft Terms of Reference - Coastal, Estuary and Floodplain Risk Management Sub-Committee758

1.17 Gosford Memorial Park and Rotary Park Conservation Management Plan

Attachment 1: Draft Gosford Memorial Park and Rotary Park, CMP, May 2025_Sections 1–4 - For Public Exhibition.....764

Attachment 2: Draft Gosford Memorial Park and Rotary Park, CMP, May 2025_Sections 5–7 For Public Exhibition..... 955



Manly
Hydraulics
Laboratory



Tuggerah Lakes Flood Study Review Draft Report

Report MHL2929
20 May 2025

Prepared for: Central Coast Council



Cover Photograph: Looking across Geoffrey Road, Chittaway Point over Tuggerah Lake towards The Entrance, 3 March 2022, courtesy of Central Coast Council.

Tuggerah Lakes Flood Study Review

Draft Report

Report MHL2929
20 May 2025

Matthieu Glatz

Team Leader, Investigations

110B King Street

Manly Vale NSW 2093

T: 02 9949 0200

E: Matthieu.Glatz@mhl.nsw.gov.au

W: www.mhl.nsw.gov.au

Document Control

Issue/ Revision	Author	Reviewer	Approved for Issue	
			Name	Date
Draft Report	K. Hasler, A. Severi, A. Islam, M. Phillips	M. Glatz	B. McPherson	20/05/2025

COPYRIGHT NOTICE

This document, Tuggerah Lakes Flood Study Review 2025, is licensed under the [Creative Commons Attribution 4.0 Licence](#), unless otherwise indicated.

Please give attribution to: © Central Coast Council 2025

We also request that you observe and retain any notices that may accompany this material as part of the attribution. Notice Identifying Other Material and/or Rights in this Publication:

The author of this document has taken steps to both identify third-party material and secure permission for its reproduction and reuse. However, please note that where these third-party materials are not licensed under a Creative Commons licence, or similar terms of use, you should obtain permission from the rights holder to reuse their material beyond the ways you are permitted to use them under the [Copyright Act 1968](#). Please see the Table of References at the rear of this document for a list identifying other material and/or rights in this document.

Further Information

For further information about the copyright in this document, please contact:

Central Coast Council
PO Box 20 Wyong, NSW 2259
ask@centralcoast.nsw.gov.au
1300 463 954

DISCLAIMER

The [Creative Commons Attribution 4.0 Licence](#) contains a Disclaimer of Warranties and Limitation of Liability. In addition: This document (and its associated data or other collateral materials, if any, collectively referred to herein as the 'document') were produced by Manly Hydraulics Laboratory for Central Coast Council only. The views expressed in the document are those of the author(s), or as informed by the FRM Committee, and do not necessarily represent the views of the Central Coast Council. Reuse of this study or its associated data by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based upon the contents of this document.

Report Classification

<input checked="" type="checkbox"/>	Public	Report existence and contents publicly available.
-------------------------------------	--------	---

Report No. MHL2929

First published as draft in February 2023



Manly Hydraulics Laboratory is Safety, Environment & Quality System Certified to AS/NZS 4801, ISO 14001 and ISO 9001

110B King Street
Manly Vale NSW 2093
T 02 9949 0200 TTY 1300 301 181
ABN 20 770 707 468 www.mhl.nsw.gov.au

Foreword

The NSW Government's professional specialist advisor, Manly Hydraulics Laboratory (MHL), were commissioned by Central Coast Council to undertake a review of the Tuggerah Lakes Flood Study, improve understanding of flood behaviour and impacts, and better inform management of flood risk in the study area in consideration of the available information and relevant standards and guidelines.

The report was prepared by Kyle Hasler, Armaghan Severi, Matthew Phillips, Atikul Islam and Matthieu Glatz.

Executive summary

The original Tuggerah Lakes Flood Study was completed in 1994 by Lawson and Treloar. The study was undertaken to determine the flood behaviour events with Annual Exceedance Probabilities (AEP) of 50%, 20%, 5% and 1% as well as the Probable Maximum Flood (PMF). The model results from this study form the basis of Council's currently adopted flood planning levels for Tuggerah Lakes.

This study was followed by the Tuggerah Lakes Floodplain Risk Management Study and Plan (FRMSP) published in 2014 (WMA Water, 2014). The Tuggerah Lakes FRMSP provided management recommendations to reduce risk to life, public and private infrastructure associated with flooding.

A review and update of the original flood study investigations is now warranted for a number of reasons including recent advances in rainfall and runoff modelling techniques, significant changes in key guidelines (Australian Rainfall and Runoff, ARR 2019), an additional 30 years of monitoring data available throughout the catchment, several historical floods including a number of recent events, new interim entrance management procedures (MHL, 2022), increased development of the foreshores of Tuggerah Lakes and the benefits associated with making more informed land use planning decisions. As such, this flood study provides an updated assessment of flooding in the Tuggerah Lakes region, with a specific focus on inundation originating from the Tuggerah Lakes themselves.

The scope of this study does not encompass catchment flooding from the Tuggerah Lakes tributaries, such as the Wyong River, Ourimbah Creek, and Wallarah Creek, or overland flooding, as these matters have been extensively addressed in the respective catchment and overland flood studies in the area. The key components of the flooding assessment included:

- Review of existing studies and data;
- Community consultation;
- Extreme value analysis;
- Hydrological and hydraulic analysis and modelling;
- Sensitivity analysis;
- Flood mapping;
- Evaluation of climate change impacts;
- Assessment of flooding consequences on the community; and
- Development of this draft flood study report.

The flood modelling included a comprehensive range of events, from the 20% to the 1 in 500 Annual Exceedance Probability (AEP) events and the Probable Maximum Flood (PMF) scenarios, representing the critical durations and patterns for the Tuggerah Lakes.

To supplement this modelling, an extreme value analysis was performed on the long-term partial peak water level series and more recent continuous water level data using the annual maximum and peak-over-threshold approaches, respectively, to estimate the flood levels for the abovementioned AEP events.

As part of the hydrologic and hydraulic modelling process, this report identified that the lack of well-rated water level stations upstream of the study area limited flow data quality for calibration, potentially introducing uncertainties regarding inflows. Furthermore, significant uncertainty was found to exist regarding the behaviour of the entrance channel, particularly in the largest flooding events, for which no detailed data for entrance behaviour are available. To enhance the reliability of the findings of a similar study, future research should consider establishing enhanced gauging stations and ensuring detailed data capture for any large events which may occur in the meantime.

A comprehensive sensitivity analysis was undertaken to evaluate the influence of key hydrologic and hydraulic parameters on flood behaviour within the Tuggerah Lakes system under the 1% AEP flood event scenario. This analysis aimed to assess the relative sensitivity of peak lake water levels and hydrograph characteristics to variations in rainfall losses, catchment response, entrance dynamics, and boundary conditions.

- **Rainfall Losses:** Varying rainfall loss parameters demonstrated the most significant impact on flood peak levels. The removal of losses led to an increase of 0.14 m in peak water level compared to baseline conditions, while doubling the losses reduced the peak by 0.13 m. These results highlight the critical influence of rainfall-runoff processes on flood magnitude.
- **Catchment Lag:** Adjustments to catchment lag ($\pm 10\%$) had a minimal impact on peak water levels (± 0.01 m), with effects primarily confined to the rising limb of the hydrograph. This indicates the timing of inflows is less critical than total runoff volume for this system.
- **Hydraulic Roughness:** Increasing or decreasing channel roughness by 20% resulted in changes of ± 0.04 m in peak lake levels. Reduced roughness facilitated quicker recession, whereas increased roughness caused higher and more prolonged flood peaks due to lower conveyance efficiency.
- **Initial lake level:** Shifting the initial lake water level to 0.2 mAHD and 0.5 mAHD resulted in variations of -0.05 m and +0.04 m respectively in peak water level. Differences were most pronounced early in the event, with convergence towards baseline levels over time.
- **Tailwater Conditions:** Tailwater level had a moderate to significant impact, depending on scenario. A high (Type C) ocean water level (2.35 mAHD) increased the lake peak by +0.12 m, reflecting tidal backflow potential. Changes in timing of peak tailwater level (± 6 hours) resulted in only minor variations (± 0.01 – 0.03 m), indicating limited sensitivity within a 12-hour alignment window.
- **Entrance Configuration:** Scenarios modifying entrance geometry and scour dynamics yielded varied results:
 - A higher initial berm increased peak levels by +0.06 m.
 - A narrower or shallower channel configuration increased peak levels by up to +0.04 m.
 - Delayed scour or slower scour duration raised peaks by up to +0.15 m.
 - A deeper final channel or faster scour duration led to reductions of up to -0.07 m.

- Pre-dredged shoals: A dredged entrance scenario (based on 2019 post-dredging survey) resulted in a negligible change (-0.01 m) to peak levels but showed slightly improved recession characteristics during the falling limb of the hydrograph.

The sensitivity analysis confirmed that rainfall losses, scour duration, and tailwater level are the most influential parameters affecting flood peak levels and hydrograph shape. While other factors such as roughness, initial conditions, and entrance configuration also play a role, their relative influence is more modest.

Analysis of the results of the hydrologic and hydraulic modelling found that flooding within the Tuggerah Lakes catchment is relatively slow onset in nature, driven by prolonged rainfall events of moderate intensity, with critical durations ranging between 72 and 144 hours. While short-duration, high-intensity events may cause overland runoff in adjoining areas, the flood mechanism of interest to this study is lake-driven. Floodwaters typically recede within hours to days following peak levels. Key flood-prone districts were identified as:

- Chittaway Point;
- Tacoma and Tacoma South;
- Tuggerawong; and
- The Entrance North behind the Wilfred Barrett Drive levee, but only in events equal to or greater than the 1% AEP, among other areas.

Flood mapping was prepared for each of the abovementioned scenarios, consisting of peak water level, depth and velocity mapping. Various oceanic inundation scenarios under present-day and future climate change scenarios were also modelled. Post-processing of these results was performed to confine the mapped results only to those areas arising directly because of lake flooding and excluding areas that may be inundated by catchment tributaries and/or overland flow. Furthermore, from these post-processed results, flood hazard, flood function, and preliminary flood emergency response classifications communities were defined as per the Floodplain Guidelines and mapped.

A preliminary impact assessment of flood consequences on the community was undertaken by identifying the number of lots, key infrastructure, and roads affected by inundation by the lakes in the various scenarios modelled. This also involved the definition of a preliminary flood planning area, where a freeboard of 0.8 m was determined to be appropriate to account for the moderate levels of modelling uncertainties and potential effects of future climate change.

Moreover, climate change scenarios projected for 2040, 2090, and 2120 indicate increases in rainfall intensity and ocean tailwater, which could exacerbate flood conditions. However, it is noted that these effects may be partially counteracted by higher hydrological losses in these future scenarios. Specifically, for the representative 1% AEP event:

- 2040 tailwater and hydrological conditions may lead to a 0.28 m rise in lake levels.
- 2070 tailwater and hydrological conditions may lead to a 0.50 m rise in lake levels.
- 2120 tailwater and hydrological conditions may lead to a 0.83 m rise in lake levels.

This study lays a robust technical foundation for ongoing flood risk management and further investigations into the Tuggerah Lakes, contributing to enhanced resilience against future flooding events.

Contents

1	INTRODUCTION	1
1.1	Background	1
1.2	Study objectives	1
1.3	Study area	2
1.4	History of flooding and rainfall	5
1.5	Land use and zoning	14
1.6	Demographic overview	16
1.7	Relevant Policies, legislation and guidance	16
1.8	Flood behaviour	23
1.8.1	Mainstream flooding	23
1.8.2	Overland flooding.....	24
1.8.3	Coastal inundation.....	24
1.8.4	Combination of flood modes.....	24
1.8.5	Observed flood prone areas	25
2	PREVIOUS STUDIES	26
2.1	Tuggerah Lakes Flood Study, Lawson & Treloar Pty. Ltd, 1994	26
2.2	Tuggerah Lakes Floodplain Risk Management Study and Plan, WMA Water, 2014 28	
2.3	Tuggerah Lakes Entrance Management Study, MHL, 2022	31
2.4	Wyong River Catchment Flood Study, BMT, 2014	31
2.5	Other studies	32
2.6	Summary	35
3	DATA COLLECTION AND REVIEW	36
3.1	Water level and rainfall data	36
3.2	Topographic data	36
3.3	Lake bathymetry and entrance channel survey data	44
3.4	Aerial photography	46
3.5	Drainage network	46
3.6	Bridges	49
3.7	Weirs	49
3.8	Flood level classifications	52
3.9	Entrance behaviour	52
3.10	Other relevant GIS information	56
4	COMMUNITY CONSULTATION.....	57
4.1	Consultation process	57
4.2	Catchment and Coast Advisory Committee	57

MHL2929- v

Classification: Public

4.3	Website	57
4.4	Letter and questionnaire	57
4.4.1	General approach	57
4.4.2	Questionnaire results.....	58
5	EXTREME VALUE ANALYSIS FOR TUGGERAH LAKE	60
5.1	Preamble	60
5.2	Data review	61
5.3	Annual maximum series analysis	61
5.3.1	Plotting position	61
5.3.2	Fitting	62
5.4	Peak over threshold analysis	63
5.4.1	Threshold selection	63
5.4.2	Declustering.....	63
5.4.3	Fitting	64
5.5	Results and discussion	65
6	HYDROLOGIC ANALYSIS	66
6.1	Model selection	66
6.2	Model setup	66
6.2.1	Catchment delineation.....	66
6.2.2	Model parameters.....	68
6.3	Model calibration and validation	71
6.3.1	Rating curve analysis	71
6.3.2	July 2022 calibration.....	78
6.3.3	June 2007 calibration	89
6.3.4	March 2021 validation	98
6.3.5	Summary	108
7	HYDRAULIC ANALYSIS	110
7.1	Model selection	110
7.2	Model setup	111
7.2.1	Model extent and grid size.....	111
7.2.2	Modelling approach	111
7.2.3	Hydraulic roughness	112
7.2.4	Structures	115
7.2.5	Boundary conditions	117
7.2.6	Entrance configuration and behaviour.....	125
7.2.7	Model limitations and assumptions.....	145
7.3	Model calibration and validation	146
7.3.1	July 2022 calibration.....	146

7.3.2	June 2007 calibration	149
7.3.3	March 2021 validation	152
7.3.4	Discussion of model calibration and validation.....	154
8	MODEL SENSITIVITY	158
8.1	Hydrologic	159
8.1.1	Rainfall losses.....	159
8.1.2	Catchment lag.....	160
8.2	Roughness	161
8.3	Initial lake water level	162
8.4	Tailwater level	163
8.4.1	Peak level	163
8.4.2	Timing	164
8.5	Entrance configuration and behaviour	165
8.5.1	Initial berm level.....	165
8.5.2	Initial channel width	166
8.5.3	Scour trigger	167
8.5.4	Scour duration	168
8.5.5	Final channel level.....	169
8.5.6	Shoals and ebb channel configuration	170
8.5.7	Entrance under elevated oceanic conditions.....	173
9	DESIGN FLOOD CONDITIONS	174
9.1	Rainfall and runoff	175
9.1.1	ARR 2019	175
9.1.2	Areal temporal patterns	176
9.1.3	Areal reduction factors.....	176
9.1.4	Rainfall losses.....	176
9.1.5	Design events	177
9.1.6	Probable Maximum Flood event.....	177
9.1.7	Critical storm duration.....	182
9.2	Entrance configuration and behaviour	187
9.2.1	Catchment flooding.....	188
9.2.2	Ocean flooding.....	192
9.3	Ocean tailwater	193
9.3.1	Catchment flooding.....	193
9.3.2	Ocean flooding.....	195
9.4	Initial water level	196
9.5	Climate change	197
9.5.1	Planning horizons and climate projections	197

9.5.2	Rainfall and runoff.....	199
9.5.3	Temporal patterns.....	200
9.5.4	Sea level rise	200
9.5.5	Other factors	200
9.5.6	Summary	201
10	DESIGN FLOOD RESULTS.....	202
10.1	Flood summary	202
10.1.1	Design floods and PMF	202
10.1.2	Ocean flooding.....	205
10.2	Flood mapping	207
10.2.1	Peak water levels and depths.....	207
10.2.2	Flood hazard.....	207
10.2.3	Preliminary flood function	208
10.2.4	Preliminary flood emergency response classifications.....	210
11	PRELIMINARY ANALYSIS OF FLOOD CONSEQUENCES ON THE COMMUNITY	212
11.1	Flood behaviour	212
11.2	Key infrastructure assets	213
11.3	Road closure	215
11.4	Preliminary flood planning area	216
	REFERENCES.....	218
	GLOSSARY	220

TABLES

Table 1.1 Summary of historical peak lake water levels (adapted from WMA Water, 2014)...	5
Table 1.2 Wyong demographic overview based on the 2021 census.....	17
Table 2.1 Design flood levels within the lakes system (Lawson & Treloar Pty. Ltd, 1994)....	27
Table 2.2: Modelled wave setup in the entrance (from Lawson and Treloar, 1994)	28
Table 2.3 Proposed floodplain risk management options (WMA Water, 2014).	29
Table 2.4 Summary of relevant studies	33
Table 3.1 Summary of relevant rainfall and water level stations	37
Table 3.2 Aerial photography details provided by the Council.....	46
Table 5.1 Annual maximum series data summary for Tuggerah Lake (1927-2024)	61
Table 5.2 EVA-based design flood level estimates for Tuggerah Lakes	65
Table 6.1 Adopted percentage impervious for each sub-catchment	68
Table 6.2 ARR 2019 hierarchical approach to design rainfall loss estimation	69
Table 6.3 NSW FFA-reconciled losses summary for Tuggerah Lakes catchments	70
Table 6.4 Selected Sydney (Terry Hills) radar imagery during the July 2022 calibration event	82
Table 6.5 Selected Newcastle radar imagery during the June 2007 calibration event.....	93
Table 6.6 Selected Sydney (Terry Hills) radar imagery during the March 2021 validation event	102
Table 6.7 Summary of the model parameters for flood calibration/validation events	109
Table 7.1 Adopted Manning's n hydraulic roughness coefficients.....	112
Table 7.2 Calibration and validation events recorded peak ocean wave conditions at Sydney	124
Table 7.3 Relevant berm surveys for calibration and validation events.....	127
Table 7.4 Relevant entrance surveys for calibration and validation events	128
Table 7.5 Satellite imagery showing the configuration of the entrance channel	132
Table 7.6 WRL photographs showing the configuration and scour of the entrance channel	137
Table 7.7 Tuggerah entrance channel width estimated by MHLFIT during historic floods...	141
Table 7.8 Example of conceptual entrance opening for July 2022 calibration event	144
Table 7.9 Summary of entrance configuration and scour parameters for calibration and validation events.....	145
Table 7.10 July 2022 calibration event peak summary	149
Table 7.11 June 2007 calibration event – peak summary	151
Table 7.12 March 2021 validation event – peak summary	153
Table 8.1 Rainfall loss sensitivity – Tuggerah Lakes peak water level	159
Table 8.2 Catchment lag sensitivity – Tuggerah Lakes peak water level	160
Table 8.3 Roughness sensitivity – Tuggerah Lakes peak water level	161
Table 8.4 Initial lake water level sensitivity – Tuggerah Lakes peak water level	162

Table 8.5 Tailwater level sensitivity – Tuggerah Lakes peak water level	163
Table 8.6 Tailwater timing sensitivity – Tuggerah Lakes peak water level	164
Table 8.7 Initial berm level sensitivity – Tuggerah Lakes peak water level	165
Table 8.8 Initial channel width sensitivity – Tuggerah Lakes peak water level	166
Table 8.9 Scour trigger sensitivity – Tuggerah Lakes peak water level.....	167
Table 8.10 Scour duration sensitivity – Tuggerah Lakes peak water level	168
Table 8.11 Final channel level sensitivity – Tuggerah Lakes peak water level.....	169
Table 8.12 Shoal and ebb channel configuration sensitivity – Tuggerah Lakes peak water level.....	170
Table 8.13 Oceanic inundation entrance sensitivity – Tuggerah Lakes peak water level	173
Table 9.1 GSDM summary for Tuggerah Lakes catchment	179
Table 9.2 GSAM summary for Tuggerah Lakes catchment	180
Table 9.3 GTSMR summary for Tuggerah Lakes catchment	181
Table 9.4 Likely critical duration range limits from hydrological modelling (with static entrance configuration)	183
Table 9.5 Critical durations for each design event	187
Table 9.6 Summary of scaling for larger event effective model entrance widths	190
Table 9.7 Summary of peak design ocean water levels for various entrance categories (South of Crowdy Head)	193
Table 9.8 Recommended combinations of catchment flooding and oceanic inundation scenarios for various design AEPs	195
Table 9.9 Oceanic inundation scenarios	196
Table 9.10 Tuggerah Lake long-term median and most frequent water levels at Long Jetty (211418) and Toukley (211418)	197
Table 9.11 Summary of key assumptions underlying the SSP scenarios.....	198
Table 9.12 Recommended rates of change (α) for rainfall depth, initial and continuing loss escalations associated with future climate change (Ball, et al., 2019).....	199
Table 9.13 Summary of projected temperatures and sea level rises, and rainfall and runoff loss increase factors associated with climate change in the relevant future years	201
Table 10.1 Tuggerah Lakes peak design level summary and comparison with previous study and EVA results.....	203
Table 10.2 Tuggerah Lakes peak flood level summary (1% AEP future climate change)....	204
Table 10.3 Tuggerah Lakes peak flood level summary (1% AEP future climate change)....	206
Table 10.4 Flood function criteria	209
Table 11.1 Number of lots affected by flooding events	212
Table 11.2 Summary of flood risk of key infrastructure assets	213
Table 11.3 Sources and quantification of modelling uncertainties.....	216
Table 11.4 Comparison of present and future 1% AEP and PMF peak Tuggerah Lakes flood levels.....	217

FIGURES

Figure 1.1 Tuggerah Lakes catchment area and study area..... 4

Figure 1.2 Flooding c. 1909 looking south from Wyong through to Tuggerah over the road and train lines. Courtesy of Central Coast Council..... 6

Figure 1.3 Damages to the original Long Jetty (built 1914 by William Henry Price) following flooding in Easter 1927. Courtesy of Central Coast Council 7

Figure 1.4 Northern railway line just north of Tuggerah Station covered by flood waters, Wyong 1927. Courtesy of Central Coast Council..... 7

Figure 1.5 The Northern Star Newspaper, Page 7, July 8 1931
<https://trove.nla.gov.au/newspaper/article/94187368>..... 8

Figure 1.6 The Canberra Times, Page 1. 20 June 1949
<https://trove.nla.gov.au/newspaper/article/2809821> 8

Figure 1.7 Parry's Jetty under flood c. 1960s. Bailey, Harold. Courtesy of Central Coast Council 9

Figure 1.8 Payne's boat shed on Tuggerah Lake at Long Jetty during flood 1960s. Bailey, Harold. Courtesy of Central Coast Council 9

Figure 1.9 Approximately 250 m north along South Tacoma Rd from Kingsland Cl, facing northwest, 5th February 1990. Courtesy of a local resident10

Figure 1.10 Marine Rescue Tuggerah Lakes Unit, Peet St, Toukley, 10th February 2020. Courtesy of a local resident10

Figure 1.11 Leonard St, The Entrance North, Facing southwest, 11th February 2020. Courtesy of a local resident11

Figure 1.12 Lakedge Ave, Berkeley Vale, immediately south of Kingsford Smith Dr, facing east, 4th March 2022. Courtesy of a local resident11

Figure 1.13 Lakedge Ave, Berkeley Vale, 100 m south of Kingsford Smith Dr intersection, Facing south, July 2022. Courtesy of a local resident12

Figure 1.14 Lakedge Ave, Berkeley Vale, Facing south along Albatross Road at the intersection of Lakedge Avenue and Albatross Road, 8th July 2022. Courtesy of a local resident12

Figure 1.15 Tuggerah Pde, Long Jetty, Facing east along Venice Street at the intersection of Tuggerah Pde and Venice Street, July 2022. Courtesy of a local resident.....13

Figure 1.16 Moui Ave, Chittaway Bay, July 2022. Courtesy of a local resident13

Figure 1.17 230 Geoffrey Road facing southwest, Chittaway Point. July 2022. Courtesy of a local resident14

Figure 1.18 Facing north along Crosby Crescent, Killarney Vale, July 2022. Courtesy of a local resident14

Figure 1.19 Land use15

Figure 1.20 SEPP (Resilience and Hazards) 2021 – Coastal Mapping.....19

Figure 3.1 Rainfall, discharge and water level stations42

Figure 3.2 Topographic data and comparison of 1 m resolution 2011-2020 LiDAR dataset against reference marks43

Figure 3.3 Distribution of the difference between 2011-2020 Gosford LiDAR data and the reference marks.44

Figure 3.4 Lake bathymetry and entrance channel survey data	45
Figure 3.5 Drainage network	48
Figure 3.6 Bridges and weirs	50
Figure 3.7 Wyong River Weir and fishway (reprinted from Newcastle Herald published on 17 October 2016)	51
Figure 3.8 Ourimbah Creek Weir and fishway (obtained from NearMap: captured on 18 August 2022)	51
Figure 3.9 Characteristic entrance conditions (MHL2811, 2022)	54
Figure 3.10 Trends in characteristic entrance conditions 1991 - 2020 using tidal harmonics and entrance width (MHL2811, 2022).....	55
Figure 4.1 Location of questionnaire respondents	59
Figure 5.1 Tuggerah Lakes AM series EVA (1927-2024).....	62
Figure 5.2 Data points selected for Tuggerah Lakes POT EVA (1986-2024)	64
Figure 5.3 Tuggerah Lakes POT EVA (1986-2024)	64
Figure 6.1 Hydrologic model catchment delineation	67
Figure 6.2 Comparison plot of gaugings and latest ratings for Wyong River at Yarramalong (211014) (WaterNSW).....	72
Figure 6.3 Comparison plot of modelled and WaterNSW-derived ratings, as extracted from the Wyong River Catchment Flood Study (2014), for the Wyong River at Yarramalong (211014).....	73
Figure 6.4 Comparison plot of gaugings and latest ratings for Wyong River at Gracemere (211009) (WaterNSW).....	74
Figure 6.5 Comparison plot of modelled and WaterNSW-derived ratings, as extracted from the Wyong River Catchment Flood Study (2014), for the Wyong River at Gracemere (211009).....	74
Figure 6.6 Comparison plot of gaugings and latest ratings for Wyong River at Wyong Fishway (WaterNSW).....	75
Figure 6.7 Comparison plot of gaugings and latest ratings for Jilliby Creek upstream Wyong River (211010) (WaterNSW).....	76
Figure 6.8 Comparison plot of modelled and WaterNSW-derived ratings, as extracted from the Wyong River Catchment Flood Study (2014), for Jilliby Creek upstream Wyong River (211010).....	76
Figure 6.9 Comparison plot of gaugings and latest ratings for Ourimbah Creek upstream Weir (211013) (WaterNSW)	77
Figure 6.10 Cumulative recorded rainfall depths during the July 2022 calibration event	78
Figure 6.11 July 2022 calibration event – recorded rainfall distribution	80
Figure 6.12 July 2022 calibration event – rain gauge zones of influence	81
Figure 6.13 2022 daily rainfall at Yarramalong	84
Figure 6.14 Comparison of simulated and observed water level data on the Wyong River for the July 2022 calibration event	87
Figure 6.15 Comparison of simulated and flow-rated level data at Ourimbah Creek upstream Weir (211013) for the July 2022 calibration event.....	88

Figure 6.16 Cumulative recorded rainfall depths during the June 2007 calibration event.....	90
Figure 6.17 June 2007 calibration event – recorded rainfall distribution.....	91
Figure 6.18 June 2007 calibration event – rain gauge zones of influence.....	92
Figure 6.19 2007 daily rainfall at Yarramalong (61220)	94
Figure 6.20 Comparison of simulated and observed water level data on the Wyong River for the June 2007 calibration event.....	96
Figure 6.21 Comparison of simulated and observed flow data at Ourimbah Creek upstream Weir (211013) for the June 2007 calibration event	97
Figure 6.22 Cumulative recorded rainfall depths during the March 2021 calibration event....	99
Figure 6.23 March 2021 validation event – recorded rainfall distribution.....	100
Figure 6.24 March 2021 validation event – rain gauge zones of influence.....	101
Figure 6.25 2021 daily rainfall at Yarramalong (61220)	104
Figure 6.26 Comparison of simulated and observed water level data on the Wyong River for the March 2021 validation event.....	107
Figure 6.27 Comparison of simulated and observed flow data at Ourimbah Creek upstream Weir (211013) for the March 2021 validation event	107
Figure 7.1 TUFLOW model Manning's n	114
Figure 7.2 TUFLOW model bridges and embankments.....	116
Figure 7.3 TUFLOW model boundary conditions	118
Figure 7.4 July 2022 calibration event – observed water level and anomaly at Patonga.....	119
Figure 7.5 June 2007 calibration event – observed water level and anomaly at Patonga ...	120
Figure 7.6 March 2021 validation event – observed water level and anomaly at Patonga ..	120
Figure 7.7 July 2022 calibration event – observed water level and anomaly at Sydney	121
Figure 7.8 June 2007 calibration event – observed water level and anomaly at Sydney.....	121
Figure 7.9 March 2021 validation event – observed water level and anomaly at Sydney....	122
Figure 7.10 July 2022 calibration event – observed significant wave height	123
Figure 7.11 June 2007 calibration event – observed significant wave height.....	124
Figure 7.12 March 2021 calibration event – observed significant wave height.....	124
Figure 7.13 Three stages of breakout (Gordon, 1990).....	126
Figure 7.14 Beach profile locations of berm entrance	127
Figure 7.15 Representative base bathymetry - pre-scour (September 2011).....	129
Figure 7.16 Representative base bathymetry - post-scour (July 2022) (TSS, 2022)	130
Figure 7.17 Photograph looking north across The Entrance, taken on the afternoon of 7 July 2022, courtesy of Central Coast Council	135
Figure 7.18 Aerial photograph of The Entrance during the June 2007 calibration event – looking west (Tuggerah Floodplain Risk Management Study, 2014).....	136
Figure 7.19 July 2022 calibration event – Tuggerah Lakes system water balance analysis	142
Figure 7.20 July 2022 calibration event – observed water levels in Tuggerah Lakes	146

Figure 7.21 July 2022 calibration event – recorded windspeed and direction at Norah Head (61366).....	147
Figure 7.22 July 2022 calibration event – difference in recorded water levels between Toukley and Long Jetty	147
Figure 7.23 July 2022 calibration event – Tuggerah Lake water level (Long Jetty and Toukley)	148
Figure 7.24 July 2022 calibration event – Tuggerah Lakes Entrance water level.....	148
Figure 7.25 June 2007 calibration event – observed water levels in Tuggerah Lakes.....	149
Figure 7.26 June 2007 calibration event – recorded wind direction (black), and mean (red) and gust (green) wind speed at Norah Head (61366), starting 0900 7 June 2007	150
Figure 7.27 June 2007 calibration event – difference in recorded water levels between Toukley and Long Jetty	150
Figure 7.28 June 2007 calibration event – Tuggerah Lake water level (Long Jetty and Toukley)	151
Figure 7.29 March 2021 validation event – observed water levels in Tuggerah Lakes.....	152
Figure 7.30 March 2021 validation event – Tuggerah Lake water level (Long Jetty and Toukley)	153
Figure 7.31 July 2022 calibration event – peak flood depth	155
Figure 7.32 June 2007 calibration event – peak flood depth.....	156
Figure 7.33 March 2021 validation event – peak flood depth.....	157
Figure 8.1 Rainfall loss sensitivity – Tuggerah Lakes water level	159
Figure 8.2 Catchment lag sensitivity – Tuggerah Lakes water level.....	160
Figure 8.3 Roughness sensitivity – Tuggerah Lakes water level.....	161
Figure 8.4 Initial lake water level sensitivity – Tuggerah Lakes water level	162
Figure 8.5 Tailwater level sensitivity – Tuggerah Lakes water level.....	163
Figure 8.6 Tailwater timing sensitivity – Tuggerah Lakes water level.....	164
Figure 8.7 Initial berm level sensitivity – Tuggerah Lakes water level	165
Figure 8.8 Initial channel width sensitivity – Tuggerah Lakes water level.....	166
Figure 8.9 Scour trigger sensitivity – Tuggerah Lakes water level	167
Figure 8.10 Scour duration sensitivity – Tuggerah Lakes water level.....	168
Figure 8.11 Final channel level sensitivity – Tuggerah Lakes water level	169
Figure 8.12 Shoal and ebb channel configuration sensitivity – Tuggerah Lakes water level	170
Figure 8.13 Satellite imagery of dredged entrance (December 2018, NearMap)	171
Figure 8.14 Overview of processes at Tuggerah Lakes Entrance (Figure 2.8, Tuggerah Entrance Management Study, 2022), with dredge target area shaded in red.....	172
Figure 8.15 Oceanic inundation entrance sensitivity – Tuggerah Lakes water level.....	173
Figure 9.1 Comparison of recurrence frequency terminologies and preferred usage	174
Figure 9.2 Temporal pattern ranges	176
Figure 9.3 Recommended regional estimates for the AEP of PMP (Ball, 2019).....	177

Figure 9.4 Simulated and adopted idealised static Tuggerah Lakes entrance rating curves	183
Figure 9.5 Heavily constricted (top) and open (bottom) peak entrance discharge for all IFD design events	184
Figure 9.6 Heavily constricted (top) and open (bottom) critical duration analysis for the 1% AEP design event.....	185
Figure 9.7 Heavily constricted (top) and open (bottom) temporal pattern hydrograph comparison for the critical duration 1% AEP design event.....	186
Figure 9.8 Extrapolation of effective entrance width for larger (< 5% AEP) flood events.....	190
Figure 9.9 Geotechnical (bore hole) data as extracted from the engineering drawings for The Entrance Bridge (TfNSW, 1967)	191
Figure 9.10 HHWS(SS) ocean water levels (South of Crowdy Head) (mAHD)	194
Figure 9.11 5% AEP ocean water levels for various entrance categories (South of Crowdy Head) (mAHD)	194
Figure 9.12 1% AEP ocean water levels for various entrance categories (South of Crowdy Head) (mAHD)	194
Figure 9.13 Tuggerah Lake water level exceedance curve and frequency distribution at Long Jetty (211418) (DCCEEW, 2025)	197
Figure 9.14 Tuggerah Lake water level exceedance curve and frequency distribution at Toukley (211418) (DCCEEW, 2025).....	197
Figure 9.15 Projected temperature increases associated with AR6 socioeconomic pathways relative to 1961-1990 and their associated uncertainty (Ball, et al., 2019)	199
Figure 9.16 Projected sea level rise under the median confidence SSP2-4.5 scenario at Sydney (Fort Denison), with shaded uncertainty envelopes	200
Figure 10.1 Tuggerah Lakes design hydrographs (20% AEP to 1 in 500 AEP).....	202
Figure 10.2 Tuggerah Lakes PMF design hydrograph.....	202
Figure 10.3 Tuggerah Lakes design hydrographs (1% AEP with future climate change)	204
Figure 10.4 Tuggerah Lakes oceanic inundation hydrographs (present conditions).....	205
Figure 10.5 Tuggerah Lakes oceanic inundation hydrographs (2040 conditions).....	205
Figure 10.6 Tuggerah Lakes oceanic inundation hydrographs (2070 conditions).....	206
Figure 10.7 Tuggerah Lakes oceanic inundation hydrographs (2120 conditions).....	206
Figure 10.8 General flood hazard vulnerability curves (AIDR, 2017).....	207
Figure 10.9 Increase in 1% AEP lake level for various flood fringe/storage depth thresholds	209
Figure 10.10 Flow chart for determining flood emergency response classifications (DPE, 2023d).....	210

1 Introduction

1.1 Background

Under the NSW Flood Prone Land Policy and Flood Risk Management Manual (2023; superseding the 2005 Floodplain Development Manual), the management of flood liable land remains the responsibility of local government.

The original Tuggerah Lakes Flood Study was completed in 1994 by Lawson and Treloar. The study was undertaken to determine the flood behaviour events with Annual Exceedance Probabilities (AEP) of 50%, 20%, 5% and 1% as well as the Probable Maximum Flood (PMF). The model results from this study form the basis of Council's currently adopted flood planning levels for Tuggerah Lakes.

This study was followed by the Tuggerah Lakes Floodplain Risk Management Study and Plan (FRMSP) published in 2014 (WMA Water, 2014). The Tuggerah Lakes FRMSP provided management recommendations to reduce risk to life, public and private infrastructure associated with flooding. A number of recommendations were made to reduce flood risk including adaptation planning for foreshore suburbs, flood emergency management planning, development of public education and awareness, adoption of development controls and formalising an entrance management strategy. The FRMSP was based on modelled flood behaviour from the Tuggerah Lakes Flood Study (Lawson and Treloar, 1994).

A review and update of the original flood study investigations is now warranted for a number of reasons including recent advances in rainfall and runoff modelling techniques, significant changes in key guidelines (Australian Rainfall and Runoff, ARR 2019), additional 29 years of monitoring data available throughout the catchment, several historical floods including a number of recent events, new interim entrance management procedures (MHL, 2022), increased development of the foreshores of Tuggerah Lakes and the benefits associated with making more informed land use planning decisions.

1.2 Study objectives

The objective of this study is to improve understanding of flood behaviour and impacts, and better inform management of flood risk in the Tuggerah Lakes study area in consideration of the available information, and relevant standards and guidelines. The aim of this study is to inform:

- Relevant government information systems;
- Government and strategic decision makers on flood risk;
- The community;
- Flood risk management planning for existing and future development;
- Emergency management planning for existing and future development, and strategic and development scale land-use planning to manage growth in flood risk; and
- Other key stakeholders (including utility providers and the insurance industry) on flood risk.

The outputs of the study may be able to assist this by facilitating information sharing on flood

risk across government and with the community, and providing a better understanding of:

- The variation in flood behaviour, flood function, flood hazard and flood risk in the study area;
- Impacts and costs for a range of flood events or risks on the existing and future community;
- Impacts of changes in development and climate on flood risk;
- Emergency response situation and limitations; and
- Effectiveness of current management measures.

1.3 Study area

The Tuggerah Lakes system is located within the traditional boundaries of Darkinjung (Darkinyung) land on the Central Coast of NSW, approximately 80 km north of Sydney. The study area comprises three main interconnected lakes including Tuggerah Lake, Budgewoi Lake and Lake Munmorah. Tuggerah Lake is the largest of the three lakes and is connected to Budgewoi Lake and Lake Munmorah by narrow channels at Gorokan and Budgewoi. The lakes system is connected to the ocean via a tidal channel through the barrier dune at The Entrance. The condition of the entrance of Tuggerah Lakes, where flows exchange to/from the ocean, is dynamic and subject to entrance sediment infilling and scour, such that the estuary is classified as an Intermittently Closed and Open Lakes and Lagoon (ICOLL).

The Tuggerah Lakes system covers a total catchment area of approximately 790 km² of which approximately 10% is covered by lakes. Wyong River, Ourimbah Creek, Tumbi Umbi Creek and Wallarah Creek are the major catchments contributing to the lakes system. Wyong River, Ourimbah Creek and Tumbi Umbi Creek drain catchment areas of approximately 447 km², 160 km² and 14 km² respectively to the southern end of Tuggerah Lake, and Wallarah Creek drains a catchment area of around 32 km² into Budgewoi Lake.

Prior to European settlement in 1825, Aboriginal peoples occupied the Tuggerah Lakes catchment area (Darkinjung land) with minimal environmental impact, utilising the lakes and adjacent beaches for the collection of a variety of seafood (CSIRO, 1999). After European settlement in the 19th and 20th centuries, properties were acquired (originally for farming purposes) around the low-lying foreshore of the lakes. Nowadays, around 80% of the shorelines of the Tuggerah Lakes are urbanised, primarily in the form of residential land use, and is susceptible to flood damages. In 2014, it was estimated that approximately 1,300 buildings would be impacted by the 1% AEP lake flood event and with a long-term annual average damage for the foreshore properties surrounding Tuggerah Lakes of \$2.2 million (WMA Water, 2014).

Ocean tides in the region are microtidal with mean spring and neap ranges of 1.3 m and 0.8 m, respectively. The regional wave climate is of moderate to high energy. The tidal range within the lakes is relatively small in the order of centimetres and average lake levels vary between 0.2 to 0.3 m AHD due to the dynamic constriction of the entrance channel and shoals. Over the past 29 years, recorded lake levels at Long Jetty (211418) typically vary between 0.09 and 0.50 m AHD (90% of the time) and have been measured to reach in excess of 1.75 m AHD during flood events.

The study area is presented in **Figure 1.1**. Hydrologic modelling for the present study covered the full catchment area presented, while hydraulic modelling and analysis of flood impacts and behaviour in the present study was focussed on flooding of the Tuggerah Lakes system in lower reaches of the catchment, with elevations less than approximately 3 mAHD.




Figure 1.1

**Tuggerah Lakes
catchment and
study area**

Legend

- ▭ Catchment boundary
- ▭ 3 m AHD Contour
- Primary tributaries

Report MHL2929

**Tuggerah Lakes Flood
Study Review**



**Manly
Hydraulics
Laboratory**

1.4 History of flooding and rainfall

Historical records and observations provide valuable evidence of historic flood behaviour in the Tuggerah Lakes catchment in response to heavy rainfall. Flood events have had a history of resulting in inundation of land and, in some instances, built assets. A summary of historical peak lake water levels for Tuggerah Lakes is shown in **Table 1.1**. It is noted that accurate gauged water levels measurement commenced in Tuggerah Lakes in 1985 after installation of the Toukley and Killarney Vale gauges. Prior lake water levels are based on historical observations.

The largest known flood occurred on the 18 June 1949, reaching a lake level of approximately 2.1 m AHD. Lake flood levels are estimated to have equalled or exceeded 1.5 m AHD at least 14 times over the last 100 years and five times since gauged water level records began in 1985 (February 1990, June 2007, February 2020, March 2021 and July 2022). Recent flooding in July 2022 resulted in lake levels reaching 1.76 m AHD at Toukley and Wallarah Creek Bridge gauges, the highest on record since gauging began in 1985.

Table 1.1 Summary of historical peak lake water levels (adapted from WMA Water, 2014)

Event	Historical recorded peak lake level (m AHD)	Measured gauge peak lake level (m AHD)		
		Toukley	Walarah Creek Bridge	Long Jetty
18 June 1949	2.10	-	-	-
April 1946	1.88	-	-	-
2 May 1964	1.87	-	-	-
April 1927	1.81	-	-	-
1931	1.81	-	-	-
6 July 2022	-	1.76	1.76	1.72
11 Feb 2020	-	1.66	1.66	1.67
10 June 2007	-	1.68	1.65	1.64
4 February 1990	-	1.61	-	-
4 March 1977	1.59	-	-	-
22 March 2021	-	1.50	1.49	1.52
1963	1.53	-	-	-
1953	1.49	-	-	-
1941	1.48	-	-	-

Notes: Historical records obtained from WMA Water (2014) and Lawson and Treloar (1994). It is likely that several floods prior to 1970 may not have been recorded. Gauged lake levels can be subject to wind and wave setup effects.

Photographs of recent and historical flood events have been provided by community members as part of the community consultation process and from Central Coast Council's Library Service. Selected photos and historical accounts of past flood events (chronologically listed) are shown below (Figure 1.2 to Figure 1.18).

A detailed summary of historical flood information and accounts spanning 1867 to 1992 is provided in *Tuggerah Lakes Flood Study Compendium of Data. New South Wales. Coast and Rivers Branch. October 1992.*

Also associated with past flood events is historical information describing changing entrance conditions and past interventions at the dynamic entrance channel opening to the ocean. This information is summarised in the *Tuggerah Lakes Entrance Management Study, MHL, 2022.*

Additional flood history in various upstream catchments and tributaries feeding into Tuggerah Lakes is documented in previous flood studies (see Section 2).



Figure 1.2 Flooding c. 1909 looking south from Wyong through to Tuggerah over the road and train lines. Courtesy of Central Coast Council



Figure 1.3 Damages to the original Long Jetty (built 1914 by William Henry Price) following flooding in Easter 1927. Courtesy of Central Coast Council



Figure 1.4 Northern railway line just north of Tuggerah Station covered by flood waters, Wyong 1927. Courtesy of Central Coast Council

MHL2929- 7
Classification: Public

FEARS OF FLOOD

There is considerable apprehension among residents of Tuggerah, Wyong, Gosford and Woy Woy as a result of the flood waters again rising. Early yesterday afternoon the floods showed signs of receding, but towards evening commenced to rise again. Three feet of water washed through some homes at Woy Woy, and although the position was slightly easier this morning grave fears are entertained unless the rain ceases. The Wyong River burst its banks at Wyong this morning, marooning many homes. Road traffic between Peats Ferry and Gosford is suspended owing to washaways.

The rainfall in Sydney for the 24 hours ended 9 a.m. to-day was 7.80 points, which is the highest since 1883.

Figure 1.5 The Northern Star Newspaper, Page 7, July 8 1931
<https://trove.nla.gov.au/newspaper/article/94187368>

WYONG

Families sat on the rooftops at Wyong and watched the floodwaters swirl past the houses. Hundreds were rescued by police boats. Several houses outside the town are completely submerged.

The main railway line between Sydney and Newcastle was under water for more than half a mile south of Wyong.

When the Wyong river burst its banks the floodwaters spread over hundreds of acres of low lying country.

The Pacific Highway at places was feet deep in water and traffic ceased.

Sergeant M. D. McAuliffe and Constable R. Wilson, of Wyong, rescued more than 50 people from their marooned houses in two motor launches.

The main road between Wyong and Tuggerah Lakes was flooded to a depth of five feet.

Citrus fruit growers in the Gosford district suffered heavily. More than 2,000 orange trees at one farm were under water, and the owner estimated he would lose £5,000.

Figure 1.6 The Canberra Times, Page 1. 20 June 1949
<https://trove.nla.gov.au/newspaper/article/2809821>

MHL2929- 8

Classification: Public



Figure 1.7 Parry's Jetty under flood c. 1960s. Bailey, Harold. Courtesy of Central Coast Council



Figure 1.8 Payne's boat shed on Tuggerah Lake at Long Jetty during flood 1960s. Bailey, Harold. Courtesy of Central Coast Council



Figure 1.9 Approximately 250 m north along South Tacoma Rd from Kingsland Cl, facing northwest, 5th February 1990. Courtesy of a local resident



Figure 1.10 Marine Rescue Tuggerah Lakes Unit, Peet St, Toukley, 10th February 2020. Courtesy of a local resident



Figure 1.11 Leonard St, The Entrance North, Facing southwest, 11th February 2020. Courtesy of a local resident



Figure 1.12 Lakedge Ave, Berkeley Vale, immediately south of Kingsford Smith Dr, facing east, 4th March 2022. Courtesy of a local resident

MHL2929- 11

Classification: Public



Figure 1.13 Lakedge Ave, Berkeley Vale, 100 m south of Kingsford Smith Dr intersection, Facing south, July 2022. Courtesy of a local resident



Figure 1.14 Lakedge Ave, Berkeley Vale, Facing south along Albatross Road at the intersection of Lakedge Avenue and Albatross Road, 8th July 2022. Courtesy of a local resident

MHL2929- 12

Classification: Public



Figure 1.15 Tuggerah Pde, Long Jetty, Facing east along Venice Street at the intersection of Tuggerah Pde and Venice Street, July 2022. Courtesy of a local resident



Figure 1.16 Moui Ave, Chittaway Bay, July 2022. Courtesy of a local resident



Figure 1.17 230 Geoffrey Road facing southwest, Chittaway Point. July 2022. Courtesy of a local resident



Figure 1.18 Facing north along Crosby Crescent, Killarney Vale, July 2022. Courtesy of a local resident

1.5 Land use and zoning

Land zoning GIS spatial data was provided by the Council, shown in **Figure 1.19**. The land zoning within the floodplain surrounding the lakes is classified under a range of zonings. Land use within the catchment primarily consists of Forestry (RU3), National parks and natural reserves (E1), Environmental management (E3), Primary production (RU1), Recreational waterways (W2), Environmental conservation (E2), Low density residential (R2).

MHL2929- 14

Classification: Public

